



- Uses latest type
- Adjustable headband with swivel earcups
- 3.5 mm 90° jack plug

The HS-3L are lightweight conference headphones for use in simultaneous interpretation systems with wired language channel selectors and wireless or infrared pocket receivers. They are constructed to screw fixed ball joints to provide perfect ear contact. They have high dynamic expansion drive units which provide natural sound reproduction. The impedance is matched to the Auditel channel selectors and receivers for favourable volume control characteristics. The headphones have a 1.5m single entry captive cable with a 3.5mm right angle mono jack plug.

#### Performance

Type	Dynamic
Impedance	64 ohms
Frequency response	100Hz - 12kHz (-10dB)
Nominal SPL	92dB ± 4dB
Distortion at 1 kHz	less than 3%
Rated power input	30mW
Max. power input	100mW
Weight	150 gms.

#### Architects and Engineers specification

The conference headphones shall have a fully cushioned headband with positive click stop adjustment and swivel earcups with screw fixed ball joints . The headphones shall be mono with 64 ohms dynamic drivers having a frequency response of at least 100Hz-12kHz (-10dB), nominal SPL 92dB (±4dB), distortion at 1kHz less than 3%, and maximum power input 100mW. They shall have a 1.5 m single entry cable with a 3.5 mm right angle mono jack plug and shall not weigh more than 150gms

We reserve the right to vary the specification without notice in the interest of product improvement